



**Incredibly small. Remarkably fast.**

Operator certified, secure, and cost-effective, the CM4NA modem is made for industrial M2M- and IoT-enabled solutions. With an innovative, slimline design, the CM4NA is easy to integrate into almost any form factor.

**Shorten your product development time.**

Ready to go right out of the box, the CM4NA takes connectivity off your plate, reducing time to market.

**See how our modems are used across the globe.**

Connected IO modems are used in a wide array of industries and applications, including digital signage, POS, vending machines, security, monitoring and control, and failover.

Standard:	4G LTE Category 1 with 3G fallback
Speeds:	Cat 4 150 Mbps download and 50Mbps upload
Connectivity:	One micro USB 2.0 connector for connection to host devices (V-cable included) One mini USB 2.0 connector for power One 2FF UICC card slot Two SMA connectors (for LTE)
Antennas:	Two SMA dipole antennas (included)
OS compatibility:	Linux 2.6.16 or later; Android KitKat (4.4) or later; Windows 10, 8.1, 8, 7, CE; Windows Mobile 6.5
Power input:	5V DC 0.5A
Operating temp:	-30°C to 85°C
Compliance:	LTE Category 4 3GPP Release 9
Certifications:	FCC Part 15 Class B, RoHS, PTCRB, AT&T, T-Mobile, Verizon, Industry Canada

Dimensions:	<b>Height</b>	<b>Width</b>	<b>Depth</b>	<b>Weight</b>
	3.31 inches (84 mm)	2.24 inches (57 mm)	0.7 inch (17.79 mm)	2.1 oz (60 g)

CM4NA
<b>U.S.A., Canada</b>
AT&T, T-Mobile, Verizon
<b>4G LTE</b>
Band 2 (1900 MHz)
Band 4 (1700 MHz)
Band 5 (850 MHz)
Band 12 (700 MHz)
Band 13 (700 MHz)
<b>3G</b>
Band 2 (1900 MHz)
Band 5 (850 MHz)

**IN THE BOX**

